

for:

Citizens, Developers, Engineers, Surveyors and other Interested People

To provide an itemized list of plans, documents, design calculations and other requirements for proposed subdivision roadway improvements to be submitted to VDOT for review and approval

Virginia Department of Transportation	Subdivision Submittal Checklist
Staunton District	
Revised 5/3/00	2 of 8
Subdivision Name/Phase	
Nearest State Route No.	County/Town
Plan Date	Latest Revision Date
Submittal Date	Submittal # (1st, 2nd)
Name of Firm, Designer, Phone No.	

The following items should be shown or addressed in subdivision roadway plans and documents submitted to VDOT for approval. Check appropriate blank next to each item, sign last page and submit checklist with plans. Right blank is for VDOT use only.

A. GENERAL

Yes	No	N/A	VDOT		Items
				1.	3 copies submittal letter attached outlining proposed development & discussing any waivers or modifications from VDOT Standards either being requested or previously agreed to.
				2.	3 copies of traffic study, erosion & sediment control narrative and drainage calculations, pavement & typical road section design calculations. Bound, pages numbered, no loose pages, table of contents. May combine in 1 report.
				3.	4 copies plans (if rolled, please have print facing out)
				4.	All plans are to be in accordance with VDOT's Subdivision Street Requirements, Road & Bridge Standards, Road & Bridge Specifications, Minimum Standards of Entrances to State Highways, Road Design Manual, L & D Instructional and Informational Memoranda, Drainage Manual and other applicable VDOT and Federal polices.
				5.	Plans should be self-explanatory with sufficient notes to explain the intent or purpose of the design.
				6.	Title Sheet
H	H	H		7.	Subdivision name, phase, owner w/ address and phone #
H	H	H		8.	Designer with address, phone #, and professional stamp
H	H	H		9.	Tax Map #, Magisterial District, County, City or Town
H	H	H		10.	Master Plan (show which roads built, which roads in system)
H	H	H		11.	Plat, if available, showing rights-of-way, lots & easements
H	H	H		12.	Type of development, i.e. indust., single-family residential
H	H	H		13.	Current and proposed zoning of property & adjacent parcels
H	H	H		14.	Location map with scale
H	H	H		15.	General Notes including required VDOT general notes
H	H	H		16.	Date, revision dates
\vdash	H	H		17.	Sheet Index with all sheets numbered and dated
H	H	H		18.	All lines and symbols clear & labeled; all text legible
H	H	H		19.	Existing vs. proposed items easily distinguishable
\vdash	H	H		20.	Plans must clearly indicate which roads are to be built for
Ш	Ш	Ш		20.	acceptance into VDOT's Secondary System of Highways
				1	1 acceptance into vide i a decentially dystem of riighways

Virgin	ia Depa	artment o	of Transpor	tation	Subdivision Submittal Checklis
Staunt	on Dist	rict			
Revise	ed 5/3/0	0			3 of
		В	. REVISI	ONS	
Yes	No	N/A	VDOT		Items
Yes	No	N/A	VDOT	1.	Items Letter from designer must accompany revised plans submitted to VDOT for re-evaluation describing changes made on revised plans & dates of old & revised plans. Letter should discuss any items that were not changed as requested & modifications that were made due to request of other agencies.

C. TRAFFIC ANALYSIS

Yes	No	N/A	VDOT		Items
				1.	Must be included with all subdivisions submitted.
				2.	Minimum analysis includes projected traffic count, with supporting computations (10 trips/day for single-family or per ITE's Trip Generation), for each street between intersections. Where roads can be extended in the future, analysis must consider ultimate proposed traffic.
				3.	Developer responsible for supplying sufficient information to support designs shown.
				4.	Detailed plans and studies may be required that address: * traffic analysis of existing and proposed conditions * intersection analysis including need for signalization/ channelization/turn lanes & modification to exist. signals * proposed roadway improvements to accommodate traffic generated by proposed development

D. PLAN SHEETS

Yes	No	N/A	VDOT		Items
				1.	North arrow, scale
				2.	Match lines clearly keyed to adjoining sheets w/ stations
				3.	Limits of subdivision, limits of each phase
				4.	Both edges of pavement (EP), shoulder width, and right-of-way (R/W) of connecting or adjacent streets along entire development plus 200' minimum each way. Show existing road spot elevations of both EP's and centerline @ 25' intervals near connection. Pavement design of existing streets.

Virginia Department of Transportation	Subdivision Submittal Checklist
Staunton District	
Revised 5/3/00	4 of 8

Yes	No	N/A	VDOT		Items
				5.	Existing crossovers, entrances, utilities, storm sewers, etc. that
					may be affected by proposed development.
				6.	Street names and state route numbers
				7.	Distance reference (to 0.01 mile) to nearest intersection
				8.	Centerline * stationed w/ 50' ticks, 100' or 500' labels
					* stations of begin/end, intersections, PC, PI, PT
					* curve data
				9.	Proposed EP, curb, and R/W lines and construction limits
				10.	Intersection sight distances, especially at connection to existing
					state route (field measure w/ target 10' off EP)
				11.	Posted speed limit of existing adjacent roads
				12.	Lengths of turn lanes and tapers
				13.	EP and R/W radii for cul-de-sac and flares (fillets)
				14.	Lots: * lot lines and numbers
					* entrances per Standard PE-1 or CG-9
					* entrance pipe size, type & length (can show in schedule)
				15.	Preliminary guardrail design, where needed, shown with lengths &
					terminals per VDOT standards. Final approval of layout to be
					given by VDOT's Traffic Engineering Section after grading is
	_	_			mostly complete.
Ш	Ш	Ш		16.	Relevant on-site & off-site topographic features/structures
Ц	Ш	Ш		17.	All existing and proposed utilities (See K. UTILITIES)
				18.	All exist. and prop. drainage facilities (See I. DRAINAGE)
				19.	Include Erosion & Sediment Control Plan Sheets

E. TYPICAL ROAD SECTIONS

Yes	No	N/A	VDOT		Items
				1.	Road and stations to which each applies
				2.	Proposed traffic count and design speed for each street
					(can be shown in a schedule)
				3.	Centerline and R/W width
				4.	Width & slope of pavement, shoulder, ditch, etc; type shoulder
				5.	Curb type, sidewalk, utility strip, etc., if applicable
				6.	Cut and fill slopes
				7.	Pavement design in accordance with VDOT's: Subdivision Street Requirements, Superpave Asphalt Design Mixes and Pavement Design Guide for Subdivision & Secondary Roads in Virginia (Minimum design for any road is 8" 21-B Aggregate with Prime & Double Seal. Minimum design for any road with curb & gutter is 8" 21-B with 2" SM-9.5A Asphalt Concrete.)
				8.	Show types, depths and application rates of all pavement and aggregate layers and prime coats.
				9.	All aggregate layers are to extend 1' beyond EP

Virginia Department of Transportation	Subdivision Submittal Checklist
Staunton District	
Revised 5/3/00	5 of 8

F. OTHER TYPICAL SECTIONS/DETAILS

	T		LVDOT		Ι,,
Yes	No	N/A	VDOT		Items
				1.	Where each applies
				2.	Pavement widening or overlays of existing roads; crossovers
				3.	Special ditches: show shape, depth, slope, lining, min/max grade. If paved, show details or VDOT Standard.
				4.	Entrances (internal, commercial or private)
				5.	Special undercut or fill measures for unsuitable material, existing ponds, sinkholes, controlled fill, etc.
				6.	Special drainage designs, structures, basins, berms, etc.
				7.	Details of all items that are not a VDOT standard or are a modification of a VDOT standard item.
				8.	Cross sections of road, drainage, or other proposed construction may be required at areas of concern such as at connections to primary roads, when work is close to exterior property lines, at other constricted areas, etc.

G. ROAD PROFILES

Yes	No	N/A	VDOT		Items
				1.	Street name
				2.	Horizontal and vertical scale and grid
				3.	Existing ground line (extended 100' minimum beyond slope tie-in)
				4.	Proposed finished grade line
				5.	Percent grade, vertical curve data including K value (=L/A)
				6.	Stations and elevations at begin/end, 50' min. intervals high & low
					points, PVC, PVI (CG), PVT, @ intersecting roads EP's and
					centerline (include super), & at sub. phase limits
				7.	Provide adequate landing
				8.	Intersection sight distances: eye = 3.5', object = 4.25'
				9.	Stopping sight distance(crest curves): eye=3.5',object=0.5'
				10.	Culverts: size, type, invert, pipe number
				11.	Storm sewer profiles and drainage structures (within R/W)
				12.	Ditch profile (where non-standard)
				13.	Water lines, sanitary sewer, and existing underground utilities
				14.	Special undercut or fill areas

Virginia Department of Transportation	Subdivision Submittal Checklist
Staunton District	
Revised 5/3/00	6 of 8

H. OTHER PROFILES

Yes	No	N/A	VDOT		Items
				1.	Special ditches, storm sewers, outfalls - extend ground line 100' minimum beyond tie-in
				2.	Entrances needing special attention, i.e. steep, constricted. (Tie proposed grade to edge of shoulder, not EP).

DRAINAGE (shown on plan & profile sheet, supplemental or detail sheet)

Items			1			
*every 5th contour highlighted & elevation clearly labeled * minimum contour interval usually two feet * shown on road plans or as separate sheet showing entire drainage system design * stationed centerline and r/w lines shown * drainage sub-areas outlined, labeled and areas shown * showing topographic features, existing buildings, etc. C. Existing and relocated streams and drainage ways. S. Existing and proposed pipes, storm sewers, and drainage structures with location, size, type, lengths, inverts, design cover, and flow arrows. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. Std CD-1 underdrains @ all sags and other appropriate spots Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. Plan, profile and typical section of all ditches other than standard roadside ditches Proposed drainage easements to natural watercourses (usually 20' minimum width). Sting drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where	Yes	No	N/A	VDOT		Items
* minimum contour interval usually two feet * shown on road plans or as separate sheet showing entire drainage system design * stationed centerline and r/w lines shown * drainage sub-areas outlined, labeled and areas shown * showing topographic features, existing buildings, etc.					1.	
* shown on road plans or as separate sheet showing entire drainage system design * stationed centerline and r/w lines shown * drainage sub-areas outlined, labeled and areas shown * showing topographic features, existing buildings, etc. 2. Existing and relocated streams and drainage ways. 3. Existing and proposed pipes, storm sewers, and drainage structures with location, size, type, lengths, inverts, design cover, and flow arrows. 4. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						
drainage system design * stationed centerline and r/w lines shown * drainage sub-areas outlined, labeled and areas shown * showing topographic features, existing buildings, etc. 2. Existing and relocated streams and drainage ways. 3. Existing and proposed pipes, storm sewers, and drainage structures with location, size, type, lengths, inverts, design cover, and flow arrows. 4. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						
* stationed centerline and r/w lines shown * drainage sub-areas outlined, labeled and areas shown * showing topographic features, existing buildings, etc.						
* drainage sub-areas outlined, labeled and areas shown * showing topographic features, existing buildings, etc. 2. Existing and relocated streams and drainage ways. 3. Existing and proposed pipes, storm sewers, and drainage structures with location, size, type, lengths, inverts, design cover, and flow arrows. 4. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						
* showing topographic features, existing buildings, etc. 2. Existing and relocated streams and drainage ways. 3. Existing and proposed pipes, storm sewers, and drainage structures with location, size, type, lengths, inverts, design cover, and flow arrows. 4. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						
	_	_				
structures with location, size, type, lengths, inverts, design cover, and flow arrows. 4. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where					2.	Existing and relocated streams and drainage ways.
and flow arrows. 4. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where					3.	Existing and proposed pipes, storm sewers, and drainage
 4. Proposed ditches (center of all shown graphically accurate by either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where 						structures with location, size, type, lengths, inverts, design cover,
either flow arrows, finished contours, lining symbols or other methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						and flow arrows.
methods). Show where linings begin and end. 5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where					4.	
5. Std CD-1 underdrains @ all sags and other appropriate spots 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						
□ 6. Storm sewer system w/ VDOT standard structures. Show top, rim, height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. □ 10. Erosion & sediment control measures □ 11. Stormwater management plans and computations, where						methods). Show where linings begin and end.
height, grate & invert elevations and throat lengths. 7. Plan, profile and typical section of all ditches other than standard roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						
☐					6.	
roadside ditches 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						height, grate & invert elevations and throat lengths.
 8. Proposed drainage easements to natural watercourses (usually 20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where 					7.	Plan, profile and typical section of all ditches other than standard
20' minimum width). 9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						roadside ditches
9. Existing drainage facilities possibly affected by proposed development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where					8.	
development: location, size, inverts, etc. 10. Erosion & sediment control measures 11. Stormwater management plans and computations, where						,
□ □ □ 10. Erosion & sediment control measures □ □ □ □ 11. Stormwater management plans and computations, where					9.	
Stormwater management plans and computations, where						
						Erosion & sediment control measures
necessary					11.	Stormwater management plans and computations, where
						necessary

Virginia Department of Transportation	Subdivision Submittal Checklist
Staunton District	
Revised 5/3/00	7 of 8

J. DRAINAGE COMPUTATIONS

Yes	No	N/A	VDOT		Items				
				1.	Should be self-explanatory. See A.2.				
				2.	Subdivision name, date, author, professional stamp				
				3.	In accordance with VDOT's current criteria including VDOT's				
					Drainage Manual. Discuss any methods or references used that				
_	_				are not generally used by VDOT.				
				4.	Sufficient background, supporting information and summary of				
_	_				any computer printouts submitted				
Ш	Ш	Ш		5.	Copy of USGS Topo map showing drainage patterns of area.				
Ш	Ш	Ш		6.	Discuss whether future sections are considered in design.				
				7.	Hydrology: drainage subareas to agree with contour plan, design				
					discharge calculations, pre & post-development flows.				
				8.	Hydraulics: Pipe, ditch, storm sewer & inlet computations.				
				9.	Outfall analysis (Evaluation of receiving channel/structure)				
	K. UTILITIES								

Yes	No	N/A	VDOT		Items
				1.	Show all existing underground and overhead utilities and easements, proposed water and sanitary mains, service laterals, types, sizes, and appurtenances.
				2.	Utilities should be located off R/W, where possible.
				3.	Utilities should be located out of pavement, where possible.
				4.	Adjustment of existing utilities, where needed.
				5.	Proposed utility crossings of existing roads: show location,
					alignment, size, type, encasements, lengths, crossing methods
				6.	Route utilities under culverts where possible
				7.	Set fire hydrants at R/W on lot lines, where possible.
				8.	Set manholes, valves, etc. in shoulder, utility strip or behind
					sidewalk, where possible.
				9.	Set street lights at right-of-way line, outside clear zone.
				10.	Check for conflicts between utilities, road and drainage.

L. TEMPORARY CUL-DE-SACS / ROADS TO BE EXTENDED

Yes	No	N/A	VDOT		Items
				1.	Traffic study must address ultimate projected traffic. If master plan of future area to be served is unavailable, give information on & discuss acreage, access & zoning of adjacent land. Discuss any County Comprehensive Plan available

Virgin	Virginia Department of Transportation Subdivision Submittal Checklist									
	ton Dist									
	ed 5/3/0					8 of 8				
Yes	No	N/A	VDOT		Items					
		П	1	2.	Indicate paven	nent design.				
Ħ	Ħ	Ħ		3.		ate temporary easement				
Ħ	Ħ	Ħ		4.		end existing ground line and future grade line				
		ш		''		w a satisfactory extension is possible.				
					r chicagn to chic	a canciación o poconios.				
				OUTT						
		IV	I. CURB &	GUII	ER STREETS					
Voc	No	N/A	VDOT		Items					
Yes		IN/A	VDOT	1.		dths and radii to face of curb				
H	H	H		2.						
H	H	H			Show entrance					
H	님	H		3.		12's @ intersections & other req'd. locations				
H	H	님		4.		D-1 underdrains into drop inlets				
	Ш	Ш		5.		d cul-de-sac details are usually needed to show:				
						ction (i.e. CG-11), how drainage is handled, top of evations around radii, etc.				
				6.						
	Ш	Ш		0.	Provide neces	sary drainage computations				
	N. MISCELLANEOUS									
		11	. WIIOOLLI		,00					
Yes	No	N/A	VDOT		Items					
			VDOI	1.		dentification sign is desired, provide for in easement				
	Ш	Ш		'-	off of right of w					
				2.		use of R/W is desired such as bike paths,				
	Ш	Ш		۷.		rigation system, lighting, parking, retaining walls,				
						Il details and technical specs. These may need to				
						eparate plan sheets				
				3.		special entrance road design, i.e. one way, islands,				
ш	ш	Ш		J.		Details of cluster mailbox pull-offs				
					modiano, otor i	Socialis of Glaster Hallbox Pall Glie				
	I hereby certify to the best of my knowledge that the above stated information is included in the									
cubm					my knowleage	mat the above Stated information is included in the				
submitted plans and attachments.										
		Design	er's Sianat	ure.						
	Date:									